



**Site Agent:-**  
  
Morrison Supervisor

All Traffic Management will be in accordance with Safety at streetworks and roadworks Code of Practice 2013

Dual carriageways (lane closures) restricted to 40mph or less  
 Minimum sitting distance of first sign in advance of lead in taper 300mtrs  
 Minimum taper length calculated dependant on with of hazard at a rate of 1:25 with cone spacing of 3mtrs  
 Single carriageway restricted to 30mph or less  
 Minimum sitting distance of first sign in advance of lead in taper 20mtrs  
 (lane closures) Minimum taper length calculated dependant on width of hazard at a rate of 1:13

All lead in tapers used with temp traffic lights / stop go boards / priority boards will be at 45 degrees from kerb line at 1.2 metre spacing  
 Unmarked running lanes will be maintained at 3.5 metres.  
 Unmarked walkways will be maintained at 1.5 metres or wider  
 DO NOT SCALE FROM THIS DRAWING

Drawn:- Chris Stevenson  
 christopher.stevenson@morrisonws.com  
 REF: CS201022-8  
 SCALE: N/A  
 Checked: John Davidson

**SITE ADDRESS:-**  
 GREENWAY RESERVOIR  
 Greenway Road  
 GL56 9BQ

**Key**

- Works area
- Safety zone
- 1m Road cones
- Aspect of sign view
- Barrier/Fencing
- Traffic Signal

Parking Not Bays	N
Parking Bays	N
Pedestrian Switch out	N
Junction Switch Out	N
Bus Stop	N
Zebra Crossing Bag Off	N
Disabled/Taxi/Loading Bay	N
Bus Lane Closure/Suspend	N

**SIGNS TO BE PLACE ON FENCING/BARRIER**

